



USB 2.0 A male (P2)

USB Type C male (P1)

PIN OUT

USB C TYPE(P1)	USB2.0 AM(P2)
A1, B1, A12, B12	Black 4 Gnd power
A4, B4, A9, B9	Red 1 pwr-Vbus1
A5	
B5	
A6	Green 3 UTP-Dp D+
A7	White 2 UTP-Dn D-

NOTE:

- Data Transfer: 480Mbps
- Voltages:5V Current:2.1A
- Operating Temperature:0℃~45℃
- Storage Temperature:-20℃~ 70℃
- RoHS 2.0 and REACH Compliant.

MATERIAL LIST:

④	Housing	Aluminium Black+PVC Mold Black	2	
④	Inner MOLD	LD-PE	2	
③	P1	USB 2.0 Type C Male, The Pin Gold Plating, the shell for Nickel Plating	1	
②	P2	USB 2.0 A Male Type, The Pin Gold Plating	1	
①	CABLE	USB 2.0 (28AWG TC)*1P+(24AWG TC)*2C, Jacket PVC+Cotton Braid Black, OD: 3.4±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK

Model List:

Item NO.	Length
11.02.9035	800±20mm
11.02.9036	1800±30mm
11.02.9037	3000±50mm

Item No.	11.02.9035 / 11.02.9036 / 11.02.9037
Desc.	ROLINE USB 2.0 Cable, A-C, Angled, M/M, black

		NEW	2018.03.07	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

SECOMP