


rotronic

Datenblatt - Fiche technique - Data sheet

11.03.1055




ROLINE Adapterkabel 4 pol. HDD / SATA,

ROLINE Câble d'alimentation int. serial ATA pour DD,



ROLINE Power Adapter Cable, 4-Pin HDD to SATA, 0.15 m

ROHS-COMPLIANT

LTR	REV.	DESCRIPTION	DATE
	B	ECN # 040716-1 CHANGE PACKING	07/16/04
	C	ECR # 080303-1 ADD ROHS,EDIT CONN,PACKING	03/03/08
	D	ECR # 080520-1 EDIT PACKING,ADD BARCODE NO.	05/20/08



NOTE:

- HOOK UP WIRE : UL1007 18AWG COLOR:YELLOW, BLACK, RED
- CONNECTOR :
 - P1 : 15 PIN SATA SOCKET CRIMP TYPE GOLD FLASH CONTACT 
 - P2 : 4 PIN MATE LOCK MALE
- HOUSING: JWT P/N: C5081H02-4P 
- TERMINAL: JWT P/N: C5081T0B-2 .
- HOOD: P1: MOLDED TYPE, PVC 45P, COLOR:BLACK(NK-K01)
- ELECTRICAL TEST: <1>100% OPEN SHORT & MIS WIRE TEST.
<2>>CONTACT RESISTANCE 3 Ohms MAX
<3>INSULATION RESISTANCE 20M Ohms MIN
- PACKING: EACH PC / POLYBAG + HEADER CARD(FDRAG04)+P/N LABEL
50 PCS / INNER CARTON WITH OUTER CARTON LABEL,
INNER CARTON SIZE: 230*220*120mm,
6 INNER CARTONS / MASTER CARTON,
MASTER CARTON SIZE: 460*380*245mm.
- 6.BAR CODE NO.: 7611990148547.

P1	P2
1, 2, 3	<u>YELLOW</u> 1
4, 5, 6	<u>BLACK</u> 2
7, 8, 9	<u>RED</u> 4
10, 11, 12	<u>BLACK</u> 3

Tolerance	Inch	M/M	Title		
X	.015	.30	Rotronic Co., Ltd.		
.XX	.010	.10	SERIAL ATA POWER SUPPLY CABLE		
.XXX	.005	.05	Customer P/N: 11.03.1055		
Draw	FANNIE 05/20/08		App'd	Customer T-RAG	
Check	Engr		Scale	NONE	Units
			Dwg No.	150-0327	REV:D
			Sheet	1/1	