


PINOUT DIAGRAM:



NOTES:

- 1) P1 & P2 HD 15 Male / Male
- 2) FULLY COPPER FOIL SHIELD 360° P1 & P2.
- 3) CABLE JACKET : PVC BLACK COLOR
- 4) MOLDED HOOD : BLACK COLOR
- 5) REMOVED PIN 9, PIN 15 IS NOT CONNECTED
- 6) RoHS & REACH COMPLIANT

4	OUTER JACKET PVC 45Pa BLACK(1101) (RoHS)
3	INNER JACKET:PE (RoHS)
2	HDB15M BLUE SOLDER TYPE TERMINAL GOLD FLASH W/O 9 PIN (RoHS)
1	2919(28#1C+S+MY)3+26#7C+AEB(AL/MG) OD8.0MM 15000MM BLACK(1101) (RoHS)

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1°	
DIMENSIONS	TOLERANCE
0.00 TO 30.00mm	±0.10mm
30.01 TO 80.00mm	±0.13mm
80.01 TO 150.00mm	±0.15mm
150.01mm	±0.20mm
MATERIAL	MATERIAL
FINISH	FINISH

rotronic

ROLINE HQ VGA Cable, HD 15 M/M, 15m, black

11.04.5215

SCALE / SHEET 1/1 UNIT MM SIZE A4 REV. A