



Electrical Test:

1. 100% test on computer, and pass the test on new version of MAC notebook (USB Bi-Directional Testing), solution up to 3840\*2160 @60Hz
2. Use 5V, 9V, 14.5V and 20V adapter for testing

G	45P PVC Black		G
F	PCBA (IC:FL7102+PS176)	1	PCS
E	Type C Female (Black Insulator, Gold Plated)	1	PCS
D	Type C Male (Black Insulator, Gold Plated)	1	PCS
C	HDMI 19P Male (Black Insulator, Gold Plated)	1	PCS
B	Non-UL, 30AWG*1P+24AWG*2C, OD: 3.0mm, Black PVC Jacket	1	PCS
A	UL2725 (32AWG*1P+EAM)*4C+32AWG*1P+32AWG*5C+22AWG*1C+AEB OD: 4.5mm, Black PVC Jacket	1	PCS
Number	Z-11.04.5950	Specification	Quantity Unit

ROLINE USB Type C to HDMI+Type C (PD) Cable, M/M, 1m, black

Item No. 11.04.5950

Draw *Kobe* Date: 2019.03.11

Approval

Duty F16 BOM.NO

Sample NO. 19SC007

Drawings of 1 (1) Proportion: 1:1 Unit(mm) A4

**SECOMP**