

1

2

3

4

5

6

length±xxmm

PLUG A

PIN.8

PIN.1

PLUG B

PIN.1

PIN.8

6.6±0.1

21.2±0.3

24.0±0.3

12.0±0.1

length mark

roline S/FTP PATCH CABLE 26AWG 4PR ISO/IEC 11801 & EN50288 CAT.6A LSOH XXXXXX-X

11.7±0.1

1

2

3

(1)Jacket Color:Gray(RAL7035)  
(2)Wiring:T568B


item no.	length	tolerance
21.15.1980	0.5M	+20 -0
21.15.1981	1M	+20 -0
21.15.1982	2M	+20 -10
21.15.1983	3M	+20 -10
21.15.1985	5M	+30 -20
21.15.1986	7M	+30 -20
21.15.1987	10M	+30 -20
21.15.1988	15M	+30 -20
21.15.1989	20M	+70 -30

Specification :

Material :

- RJ45 Plug : (JE P/N : PUY8850)
  - Housing : Polycarbonate, UL 94V-2, Transparent color
  - Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated
  - Contact finished : Min. 50 micro-inch Gold plated on surface contact area
  - Shield : Bronze with Nickel plated
- SR : SR-V95 FOR S/FTP Boot with nose
- Cable :
  - Jacket : LSOH
  - Conductor : 26 AWG stranded copper
  - Isolation : PE
  - Shield : Aluminum Foil Shielded for Each Pair, copper clad with steel braid
- Cable structure : S/FTP, 4 twisted pair
- Minimum Banding Radius: 50mm

item no	21.15.1980	21.15.1981	21.15.1982	21.15.1983	21.15.1985
	21.15.1986	21.15.1987	21.15.1988	21.15.1989	

Desc	ROLINE Cat 6a S/FTP Patch Cord,LSOH.Component Level,gray				
"#": Matching DIM.	DRAWING	25.Aug.2015	byz		
"*": Important DIM.	CHECK	25.Aug.2015	Jane		
Others General DIM.	APPROVAL	25.Aug.2015	Jaimy		
GENERAL TOLERANCE OF DIMENSIONS		DATE	NAME		
X.XXX ±0.005	SCALE	1/1 (A4)	UNIT	mm	
X.XX ±0.05	DRAWING NO.				
X.X ±0.1	DRAWING CLASSIFICATION		S	SHEET	1 OF 1

No.	MODIFIED AREA	ORIGINAL	MODIFY	DATE	MODIFIER
-----	---------------	----------	--------	------	----------

1

2

0

3

4

10cm

5

6

