




Datenblatt - Fiche technique - Data sheet



**21.15.2660**



ROLINE Patchkabel Kat.6 S/FTP (PiMF), Component Level, LSOH, weiss, 0,5 m

Cordon ROLINE S/FTP(PiMF) Cat.6, LSOH, Component Level, blanc, 0,5 m

ROLINE S/FTP Patch Cord Cat.6 Component Level, LSOH, white, 0.5 m



**1. ELECTRICAL TEST:**

- (1). 100% OPEN SHORT & MISS WIRE TEST;
- (2). INSULATION RESISTANCE:DC 250V 20M OHM MIN;
- (3). CONTACTOR RESISTANCE:30 OHM MAX

2. PRINTING:GHMT® roline CAT.6 S/FTP COMPONENT PATCH CORD LSZH 250MHz ISO/IEC 11801 & EN 50173-1 & ANSI/TIA-568-C.2

3. 100% Component Patch cord Test PASS

4. Minimum bending radius:60mm

**MATERIAL LIST**

⑥	LABEL	NO DRY GLUE LABEL	1PCS	
⑤	MINI TIE	PE MINI TIE (POSSESS METAL)	2PCS	
④	POLYETHYLENE BAG	POLYETHYLENE BAG	1PCS	
③	OVER MOLD	88A PVC White	2PCS	
②	CONNECTOR	RJ45 8P8C'S SHIELDED PIN GOLD PLATED 3u", SHELL PLATED NICKEL Transparent RED	2PCS	
①	CABLE	S/FTP CAT.6 26AWG (BC*1P+AL-FOIL)*4P+BRAID CABLE JACKET LSOH OD=6.2 ± 0.2MM	1PCS	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

COLOUR:White		
ITEM NO.	LENGTH (L)	TOLERANCE (T)
21. 15. 2957	300mm	±10mm
21. 15. 2660	500mm	±15mm
21. 15. 2661	1000mm	±30mm
21. 15. 2664	1500mm	±45mm
21. 15. 2662	2000mm	±60mm
21. 15. 2663	3000mm	±90mm
21. 15. 2665	5000mm	±150mm
21. 15. 2666	7500mm	±210mm
21. 15. 2667	10000mm	±300mm
21. 15. 2668	15000mm	±450mm
21. 15. 2669	20000mm	±600mm

ITEM NO.	21. 15. 2957	21. 15. 2660	21. 15. 2661	21. 15. 2662	21. 15. 2663
21. 15. 2664	21. 15. 2665	21. 15. 2666	21. 15. 2667	21. 15. 2668	21. 15. 2669
DESC.	ROLINE S/FTP PatchCord CAT. 6, LSOH, Comp. Level, White				

**SECOMP**

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

2016-10-20 A