



1. ELECTRICAL TEST:

- (1).100% OPEN SHORT & MISS WIRE TEST;
- (2).INSULATION RESISTANCE:DC 250V 20M OHM MIN;
- (3).CONTACTOR RESISTANCE:30 OHM MAX

2.PRINTING:GHMT® roline CAT.6A S/FTP COMPONENT PATCH CORD LSZH 500MHZ ISO/IEC 11801 & EN 50173-1 & ANSI/TIA-568-C.2

3.100% Component Patch cord Test PASS

4.Minimum bending radius:60mm

MATERIAL LIST

⑥	LABEL	NO DRY GLUE LABEL	1PCS	
⑤	MINI TIE	PE MINI TIE(POSSESS METAL)	2PCS	
④	POLYETHYLENE BAG	POLYETHYLENE BAG	1PCS	
③	OVER MOLD	88A PVC Pink	2PCS	
②	CONNECTOR	RJ45 8P8C'S SHIELDED PIN GOLD PLATED 3u", SHELL PLATED NICKEL Transparent Blue	2PCS	
①	CABLE	S/FTP CAT.6A 26AWG (BC*1P+AL-FOIL)*4P+BRAID CABLE JACKET LSOH OD=6.2±0.2MM	1PCS	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

COLOUR:Pink (PANTONE:212C)

ITEM NO.	LENGTH (L)	TOLERANCE (T)
21.15.2979	300mm	± 10mm
21.15.2890	500mm	± 15mm
21.15.2891	1000mm	± 30mm
21.15.2894	1500mm	± 45mm
21.15.2892	2000mm	± 60mm
21.15.2893	3000mm	± 90mm
21.15.2895	5000mm	± 150mm
21.15.2896	7500mm	± 210mm
21.15.2897	10000mm	± 300mm
21.15.2898	15000mm	± 450mm
21.15.2899	20000mm	± 600mm

ITEM NO.	21.15.2979	21.15.2890	21.15.2891	21.15.2892	21.15.2893
21.15.2894	21.15.2895	21.15.2896	21.15.2897	21.15.2898	21.15.2899
DESC.	ROLINE S/FTP PatchCord CAT.6A, LSOH, Comp.Level1, Pink				



BY	CHK	NEW REVISION RECORD MODIFICATIONS	2016-09-13	A
			DATE	REV.