

E-DAT Industry RJ45 field jack insert / RJ45 coupler insert/ USB A coupler insert
 OpDAT Industry SC-RJ/ 2SC adaptor insert MM / SC-RJ/2SC adaptor insert SM
 OpDAT Industry LC-D adaptor insert MM / LC-D adaptor insert SM

Montagehinweis / Mounting informations / Références de montage / Indicaciones de montaje / Informazioni per il montaggio

1

2

Wandstärke wall thickness 1-3 mm

V1M / V1

U-Scheibe M3/U-washer M3
 DIN EN ISO 7092
 Polyamid (PA) 6.6

3

V4

Wandstärke wall thickness > 1 mm

140310-E

Wandstärke / wall thickness 1-5 mm

4

V14M Standard

Wandstärke wall thickness > 1 mm

V14M Central

U-Scheibe M3/U-washer M3
 DIN EN ISO 7092
 Polyamid (PA) 6.6

5

V5M

Wandstärke / wall thickness > 1 mm

U-Scheibe M3/U-washer M3
 DIN EN ISO 7092
 Polyamid (PA) 6.6

6

7








8

9

10

11

D 875030A03101 899155 17.10.2017 © by METZ CONNECT • Druckfehler und technische Änderungen vorbehalten / Printing errors and technical changes reserved



		Anschluss / Connection				Anwendung / Application			
RJ45 PIN Nr./No.	Farbcode Colour code T568		DIN 47100	Industrial	10BT/ 100BT	1 Gigabit 10 Gigabit Ethernet	Token Ring	ISDN/So	Upd/ TEL
	A	B							
1	WH-GN	WH-OG	WH	YE	•	•			
2	GN	OG	BN	OG	•	•			
3	WH-OG	WH-GN	GN	WH	•	•	•		
4	BU	BU	YE	-		•	•	•	•
5	WH-BU	WH-BU	GY			•	•	•	•
6	OG	GN	PK	BU	•	•	•		
7	WH-BN	WH-BN	BU	-		•			
8	BN	BN	RD	-		•			

Weitere Demontageschritte nach Montageanleitung / further demounting steps according to the mounting instructions