



**NOTE:**  
 1. 100% OPEN SHORT, MISS WIRE TEST  
 2. PRINT BLACK WORD:  
 CAT. 6 SSTP 4×2×AWG27/7 PIMF ISO/IEC 11801  
 & EN 50173 TIA/EIA 568 B. 2-1  
 3. ROHS & Reach COMPLIANT  
 4. minimum of the bending radius is 50mm  
 (suitable for all meters)

**MATERIAL LIST:**

③	OVER MOLD	PVC COLOR: see the chart	2	
②	CONNECTOR	RJ45 8P8C SHIELDED, THE PIN GOLD PLATED 3U"	2	
①	CABLE	CAT. 6 SSTP 27AWG (7/0.135Bare Copper*IP+AL-Foil)*4PAIRS+Braid (0.12mm/5/16) AL-MG JACKET: PVC/Colour: see the chart OD: 6.2±0.2mm	1	

NO.	PARTS NAME	QT'Y	REMARK	DATE	REV.
	SPECIFICATION STANDARD			2012-01-10	A2
				2011-11-16	A1
				2010-06-29	A
BY	CHK		REVISION RECORD MODIFICATION		

**Rotronic Co., Ltd.**

VALUE Cat. 6 S/FTP Patch Cord			
ITEM NO.	APPRO BY	CHECK BY	UNIT

See The Chart  
 DATE: 2012-01-10

