

DATASHEET

Cat.6A/classEA Installation link, S/FTP, 50m on drum



General data

Robust special rubber cable drum, complete with Cat.7 S/FTP installation cable, integrated outlet Cat.6A 1 x RJ45 with dust cap and 1 x Cat.6A RJ45. Very well suited to mobile use, for exhibitions, presentations, outside broadcasting vans, measuring sections etc. A standardised installation section in accordance with structured cabling Cat.6A / Class EA.

Technical properties

AWG-size	23
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	moulded-on
Bending radius	4 x OD
Cable construction	4x2
Cable shape	rund
Cable type	S/FTP
Cabling standard	ISO/IEC 11801
Category	6A (TIA)
Colour anti-kink sleeve	black
Colour outer sheath	orange
Conductive shield	360° shield contact
Conductor Material	Copper

This datasheet was created automatically on 17-02-2026 . Technical changes reserved.



DATASHEET

Cat.6A/classEA Installation link, S/FTP, 50m on drum

Contacts	Gold plated
Dust cover	true
Fire retardant version	True
Jacket material	FRNC
Length imprint	False
Locking lever	False
Low smoke	acc. IEC61034
Model	shielded
NVP value	79 %
Oil resistant	no
Operating Temperature	-20 - 60 °C
Ozone resistance	No
Pin assignment	1:1
Raw cable	Cat.7
Resistant to chemicals	False
Temperature Range (Installation)	0 - 50 °C
Temperature Range (Operation)	-20 - 60 °C
Test voltage	1000 (V DC, 1min) core/core und core/screen
Transmission	10Gbit
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False
UV resistant	no

Available variants

ArtNr.	Bezeichnung	Length
K9201.50	Cat.6A/classEA Installation link, S/FTP, 50m on drum	50.0 m
K9201.90	Cat.6A/classEA Installation link, S/FTP, 90m on drum	90.0 m

This datasheet was created automatically on 17-02-2026 . Technical changes reserved.

